



FRONTIER® 200 Multipurpose Hose



APPLICATION: An economical air and water hose, FRONTIER® is for a wide range of industrial, construction and agricultural applications. Available in 200, 250, and 300 psi working pressures.

CONSTRUCTION TUBE: EPDM(compound)® synthetic rubber, RMA Class C (Limited Oil Resistance)

COVER: Black, Red, Yellow, Green or Blue EPDM(compound)® synthetic rubber

REINFORCEMENT: Spiral synthetic yarn, 2" is braided

TEMPERATURE: -40 °F to 190 °F (-40 °C to 88 °C)

COUPLINGS: Contact fitting manufacturer for proper fitting recommendation and coupling procedure.

BRANDING: Example: 1/2" FRONTIER® Continental Contitech 200 psi WP.

1

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20025631	3/4 in 19.10 mm	1.120 in 28.50 mm	50.000 ft	Black	200.0 psi 1.38 MPa	0.340 lb/ft 0.51 kg/m
20316536	5/8 in 15.90 mm	0.970 in 24.60 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.270 lb/ft 0.40 kg/m
20334065	5/8 in 15.90 mm	0.970 in 24.60 mm	700.000 ft	Black	200.0 psi 1.38 MPa	0.270 lb/ft 0.40 kg/m
20414668	5/8 in 15.90 mm	0.970 in 24.60 mm	328.000 ft	Black	200.0 psi 1.38 MPa	0.270 lb/ft 0.40 kg/m
20467894	3/8 in 9.50 mm	0.670 in 17.00 mm	250.000 ft	Black	200.0 psi 1.38 MPa	0.150 lb/ft 0.22 kg/m
20529986	3/8 in 9.50 mm	0.670 in 17.00 mm	250.000 ft	Black	200.0 psi 1.38 MPa	0.150 lb/ft 0.22 kg/m

<u>Item #</u>	<u>I.D.</u>	<u>Nom. O.D.</u>	<u>Length</u>	<u>Color</u>	<u>Max. Working Pressure</u>	<u>Weight</u>
20321354	3/8 in 9.50 mm	0.670 in 17.00 mm	250.000 ft	Black	200.0 psi 1.38 MPa	0.150 lb/ft 0.22 kg/m
20022883	1 1/4 in 31.80 mm	2.730 in 44.00 mm	400.000 ft	Black	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
20022884	1 1/4 in 31.80 mm	2.730 in 44.00 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
20022890	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
20022891	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Black	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
20022897	2 in 50.80 mm	2.500 in 63.50 mm	200.000 ft	Black	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m
20288283	2 in 50.80 mm	2.500 in 63.50 mm	110.000 ft	Black	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m
20022916	1 1/4 in 31.80 mm	2.730 in 44.00 mm	400.000 ft	Red	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
20022917	1 1/4 in 31.80 mm	2.730 in 44.00 mm	300.000 ft	Red	200.0 psi 1.38 MPa	0.750 lb/ft 1.12 kg/m
20022926	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Red	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
20022927	1 1/2 in 38.10 mm	1.980 in 50.30 mm	300.000 ft	Red	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
20022930	1 1/2 in 38.10 mm	1.980 in 50.30 mm	100.000 ft	Red	200.0 psi 1.38 MPa	0.860 lb/ft 1.28 kg/m
20022939	2 in 50.80 mm	2.500 in 63.50 mm	200.000 ft	Red	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m
20022941	2 in 50.80 mm	2.500 in 63.50 mm	100.000 ft	Red	200.0 psi 1.38 MPa	1.160 lb/ft 1.73 kg/m